

DATASHEET

TAUBMANS

Endure Interior Semi Gloss



Endure Interior Semi Gloss

Taubmans Endure Interior Semi Gloss offers superior performance and protection. Engineered with Nanoguard® Advanced Technology, it has an interlocking molecular structure that works to create a protective shield, so stains can be wiped away without compromising the quality of the paint or damaging the finish on your walls.



FEATURES AND BENEFITS

AUSTRALIAN MADE	Taubmans has been used to paint Australian homes since 1899. We continue to keep George Henry Taubman's legacy alive by manufacturing paint in Australia at our Villawood (NSW) and Clayton (VIC) plants. Our paints are engineered by Australian's to withstand Australia's unique conditions.
WASH RESISTANT	Superior washability - maximum washability rating acquired after 7 days.
STAIN RESISTANT	Stains can easily be wiped away without compromising the original quality of the paint.
SCRUB RESISTANT	Provides a tough and durable coating.
ANTI-MICROBIAL	Bacteria Shield Technology kills common germs and bacteria, such as staphylococcus aureus, escherichia coli, salmonella and listeria. This technology will last the life of the paint.
ASTHMA & ALLERGY FRIENDLY	Approved by the National Asthma Council Australia's Sensitive Choice® program. Products approved by the Sensitive Choice Program may help people with asthma and allergies.
LOW VOC & ODOUR	Meets environmental standards of low VOC coatings; assisting specifiers in building green without sacrificing coating performance.
INHIBITS MOULD & MILDEW	Taubmans paints provide protection against the growth of mould and mildew on painted surfaces. It is ideal for walls and ceilings in bedrooms, kitchens and bathrooms as well as damp, high humidity areas.
NANO GUARD® ADVANCED TECHNOLOGY	Taubmans Endure is engineered with Nanoguard® Advanced Technology, which provides maximum protection for walls. It has an interlocking molecular structure that creates a protective shield so everyday dirt and stains can be wiped away without compromising the quality of the paint. It is one of the most advanced paint technologies available today.
CLEANS UP IN WATER	Paint and used brushes/rollers can be cleaned up in water.
FAST DRYING	Assists project completion timelines with fast drying properties.
EASY TO APPLY	The superior application properties of Taubmans Endure make it exceptionally easy to apply and leaves every paint job with a professional finish.
EXCELLENT FLOW PROPERTIES	Ease of application, good flow properties & minimal roller splatter.
HIGH OPACITY	Exceptional hiding properties.

DATASHEET

PRODUCT SPECIFICATIONS

GLOSS LEVEL	20 - 30%
SPECIFICATIONS MET	AS3730.2, AS2311, APAS0260/2
VOC LEVELS	<15g per litre
CLEAN UP	Water: Scrape excess paint from equipment into a separate container. Wash up with water. Do not dispose of paint or wash water in drains or sewers
DRY TIMES: TOUCH DRY	30 minutes
DRY TIMES: RECOAT	2 hours at 25°C (allow 4 hours in cold or humid areas)
APPLICATION METHODS	Brush, Roller, Spray
DRY FILM THICKNESS	25 - 30 microns
WET FILM THICKNESS	60 - 65 microns
RECOMMENDED COATS	2
COVERAGE	Up to 16 square metres per litre (depending on substrate)
COLOUR RANGE	Extensive colour range. Refer to Taubmans Architectural/Specifier Colour Systems.

SURFACE PREPARATION

GENERAL INTERIOR	Surfaces must be clean, dry and free from all surface contamination. Treat mould with bleach then rinse with fresh water. Fill in surface defects with suitable filler, putty or sealant. Avoid using masking tape on wall and ceiling paints. For wallpaper, make sure all glue residue is sanded and washed off from the surface before applying one coat of Taubmans 3 in 1 Prep.
NEW WORK	Apply one coat of Taubmans 3 in 1 Prep on paper faced plasterboard, fibre cement, masonry & timber. Seal new or bare plaster with a Plaster Sealer first. Seal bare wallboards or Gyprock with prep coat first. Allow masonry, cement render and mortar to cure for 28 days before painting.
PREVIOUSLY PAINTED	Remove all loose and flaking paint by scraping or sanding previously painted areas until smooth. To ensure an even surface when painting over patchy or contrasting colours, apply one coat of Taubmans 3 in 1. Spot prime bare areas in accordance with directions for preparation and new work.
AFTER PAINTING	Avoid exposure to steam for 48 hours. Surface may be washed after 7 days, but always avoid abrasive cleaners.

APPLICATION

STIRRING	Stir paint with a wide flat stirrer in a circular lifting motion for at least 5 minutes before use. It is a requirement to stir paint before use to ensure that the colour tints are dispersed evenly throughout the paint. Continue stirring at regular intervals during application. Where more than one can of the same colour and product is required for a job, mix the contents of all the cans together to ensure colour consistency.
CURING	Avoid exposure to steam and condensation for 48 hours after painting.
PAINT BRUSH/ROLLER	Stir paint in a circular lifting motion for 5 minutes before use. Apply two coats by roller, brush or spray gun, with 2 hours between each coat. Paint the corners and edges with a narrow brush. Roll up to the edges using a quality synthetic or lambswool 10 - 12mm nap roller.
AIR SPRAY	Apply with good ventilation only when air and surface temperatures are above 10°C. <ul style="list-style-type: none"> • Ensure the paint satisfactorily atomises (thinning up to 10% with water may be required) • Choose appropriate tip size (0.013 - 0.019 thou) • Back roll all coats
AIRLESS SPRAY	Apply with good ventilation only when air and surface temperatures are above 10°C. <ul style="list-style-type: none"> • Ensure the paint satisfactorily atomises (thinning up to 10% with water may be required) • Choose appropriate tip size (0.013 - 0.019 thou) • Back roll all coats

DATASHEET

MAINTENANCE

The maintenance requirements and durability will determine the life-cycle costs of the paint. Good quality paints have a long life on interior surfaces and repainting is generally only required when staining or soiling has occurred or when there is a desire for a new colour. Stain resistance is a products ability to resist all types of stains soaking into the paint film and leaving a permanent mark.

- Scrub resistance is a measure of the paints film toughness. It is measured by the number of scrubs it takes to break through the film of the paint.
- Washability: Washability refers to the gloss change of the painted film, after it has been washed with a soapy solution.

With excellent stain resistance, high scrub resistance and excellent washability, the performance of Taubmans Endure under these challenging maintenance requirements puts it at the forefront of paints for longevity and durability, whilst still maintaining an exceptional quality of surface finish.

PRECAUTIONS

STORAGE INFORMATION

Store in original container protected from direct sunlight in a dry, cool and well-ventilated area. Do not store below 5°C temperature. Keep containers sealed when not in use.

SAFETY INFORMATION

Keep out of reach of children. Keep lid on when not in use.

FIRST AID

IF SWALLOWED Drink plenty of water. Always seek medical advice.
EYE CONTACT Flush with plenty of water. Always seek medical advice.
SKIN CONTACT Wash with soap and water. Always seek medical advice.
AUSTRALIA 24 hour Medical Emergency Response Service: 1800 883 254 Taubmans Customer Service: 131 686
Further information: www.taubmans.com.au

ENVIRONMENTAL
INFORMATION

Do not pour leftover paint down the drain. Dispose of contents and container in accordance with local, regional, national and international regulations. For responsible disposal of paint and packaging visit paintback.com.au

VENTILATION

Ensure adequate ventilation, keep floors and furniture covered. Keep lid on containers when not in use.

SAFETY DATA SHEET

SDS available from the Taubmans Website www.taubmans.com.au/painters/endure-interior

DISCLAIMER

Any information provided by PPG Industries Australia Pty Ltd and its related entities relating to PPG products or their use and application (for example, information contained in a PPG paint system, Specification, or Data Sheet) is accurate and reliable at the time of publication. However, such information is general in nature. You must ensure that the information is current and suitable for the specific conditions for your project. If you need technical information for your circumstances, you should contact Taubmans Customer Service. PPG Industries Australia Pty Ltd and its related entities are not liable for any loss (including indirect, special or consequential loss, or loss of profits), expense, or damage suffered in connection with (a) such information, or (b) any information provided by a third party (including where that information is provided on a PPG website). Nothing in this disclaimer restricts, excludes or modifies or purports to restrict, exclude or modify any statutory rights under any applicable law including the Competition and Consumer Act 2010 (Cth) or the operation of any express guarantee.

CUSTOMER SERVICE/COMPANY CONTACT

Taubmans Customer Service: 131 686 Further information: www.taubmans.com.au