

DATASHEET

TAUBMANS®

All Weather® Exterior Gloss



Taubmans All Weather Exterior Gloss

Taubmans All Weather Exterior Gloss offers superior performance against leading competitors, making it the perfect choice for exterior surfaces. Engineered with Nanoguard® Advanced Technology, it has an interlocking molecular structure that works to create a protective shield, so dirt can be washed away without compromising the quality of the paint or damaging the finish. It comes with a lifetime guarantee* against peeling, flaking and blistering.



USES

All exterior walls (recommended for weatherboards, roof and trims), cement render / masonry, timber, galvanised iron, PVC piping and steel.
Not suitable for surfaces used to collect drinking water.

FEATURES AND BENEFITS

AUSTRALIAN MADE	Taubmans has been used to paint Australian homes since 1899. We continue to keep George Henry Taubman's legacy alive by manufacturing paint in Australia at our Villawood (NSW) and Clayton (VIC) plants. Our paints are engineered by Australians to withstand Australia's unique conditions.
UNIQUE DIRT SHEDDING FORMULA	Dirt resistant – enables surfaces to remain cleaner for longer and any ingrained dirt to be easily washed from the surface.
UV PROTECTION	Advanced UV protection helps to prevent chalking and fading.
INHIBITS MOULD & MILDEW	Taubmans paints provide protection against the growth of mould and mildew on painted surfaces.
NANOGUARD® ADVANCED TECHNOLOGY	Taubmans All Weather Exterior is engineered with Nanoguard Advanced Technology, which provides maximum protection for exterior surfaces against everyday dirt and stains. The interlocking molecular structure utilises small and large particles to form a strong protective shield, so the surface can be cleaned without compromising the quality of the paint.
CLEANS UP IN WATER	Paint and used brushes/rollers can be easily cleaned up in water.
FAST DRYING	Assists project completion timelines with fast drying properties. Recoat after 2 hours.
EASY TO APPLY	The superior application properties of Taubmans All Weather Exterior make it exceptionally easy to apply and leaves every paint job with a professional finish.
EXCELLENT FLOW PROPERTIES	Ease of application, good flow properties and minimal roller splatter.
HIGH OPACITY	Exceptional hiding properties.
SELF PRIMING	No primer needed (on most surfaces).
LIFETIME GUARANTEE*	Guaranteed against blistering, flaking or peeling if applied on suitable and properly prepared surfaces, according to painted directions.

DATASHEET

PRODUCT SPECIFICATIONS

GLOSS LEVEL	70 - 75%
SPECIFICATIONS MET	AS3730.10, APAS 0280/1
VOC LEVELS	<52g per litre
CLEAN UP	Water: Scrape excess paint from equipment into a separate container. Wash up with water. Do not dispose of paint or wash water into drains or sewers.
DRY TIMES: TOUCH DRY	30 minutes
DRY TIMES: RECOAT	2 hours at 25°C (allow 4 hours in cold or humid areas)
APPLICATION METHODS	Brush, Roller, Spray
DRY FILM THICKNESS	25 - 30 microns
WET FILM THICKNESS	60 - 65 microns
RECOMMENDED COATS	Minimum two coats. Apply a third coat for superior performance (depending on substrate - coverage will be lower on rough or absorbent surfaces.
COVERAGE	Up to 16 square metres per litre (depending on substrate)
COLOUR RANGE	Extensive colour range. Refer to Taubmans Architectural/Specifier Colour Systems.

SURFACE PREPARATION

GENERAL EXTERIOR	Surfaces must be clean, dry and free from all surface contamination. Treat mould with bleach then rinse with fresh water.
NEW WORK	TIMBER Weathered (greyed) timber must be sanded to the original timber surface. Tannin rich timbers such as cedar should be primed with Taubmans 3 in 1 Prep or a suitable Taubmans oil based wood primer.
	GALVANISED IRON Thoroughly degrease new surfaces. Weathered surfaces should be thoroughly cleaned before painting. For structural galvanised iron, abrade with 240 grade paper to remove chemical treatments and allow full adhesion.
	CEMENT RENDER / MASONRY Allow masonry, cement render and mortar to cure for 28 days before painting.
	STEEL Remove rust and prime with a suitable Taubmans iron & steel primer or White Knight Rust Guard® Metal Primer.
	ZINCALUME® STEEL Wash with water and mild detergent. Surface must be clean and dry. Apply one coat of Taubmans 3 in 1 Prep.
REPAINT	Remove all loose and flaking paint. Spot bare areas with Taubmans All Weather Exterior Gloss or the appropriate primer. Apply Taubmans 3 in 1 Prep to aged enamel systems to provide intercoat adhesion. Thoroughly sand new or unweathered Colorbond®.
AFTER PAINTING	Avoid exposure to steam for 48 hours. Surface may be washed after 7 days, but always avoid abrasive cleaners.

DATASHEET

APPLICATION

STIRRING	Stir paint with a wide flat stirrer in a circular lifting motion for at least 5 minutes before use. It is a requirement to stir paint before use to ensure that the colour tints are dispersed evenly throughout the paint. Continue stirring at regular intervals during application. Where more than one can of the same colour and product is required for a job, mix the contents of all the cans together to ensure colour consistency.
CURING	Avoid exposure to steam and condensation for 48 hours after painting.
PAINT BRUSH/ROLLER	Apply two coats by roller, brush or spray gun, with 2 hours between each coat. Paint the corners and edges with a narrow brush. Roll up to the edges using a quality synthetic or lambswool 10 - 12mm nap roller.
AIR SPRAY	Apply with good ventilation only when air and surface temperatures are above 10°C. <ul style="list-style-type: none"> • Ensure the paint satisfactorily atomises (thinning up to 10% with water may be required) • Choose appropriate tip size (0.013 - 0.019 thou) • Back roll all coats
MAINTENANCE	Painted exterior surfaces can deteriorate over time when exposed to elements of nature, such as the harsh Australian sun. To maximise the look of the paint, it is recommended that the surface is washed regularly to remove dirt and chalk.

PRECAUTIONS

STORAGE INFORMATION	Store in original container protected from direct sunlight in a dry, cool and well-ventilated area. Do not store below 5°C. Keep containers sealed when not in use.
SAFETY INFORMATION	Keep out of reach of children.
FIRST AID	IF SWALLOWED: Drink plenty of water. Always seek medical advice. EYE CONTACT: Flush with plenty of water. Always seek medical advice. SKIN CONTACT: Wash with soap and water. Always seek medical advice. AUSTRALIA: 24 hour Medical Emergency Response Service: 1800 883 254 Taubmans Customer Service: 131 686 Further information: taubmans.com.au
ENVIRONMENTAL INFORMATION	Do not pour leftover paint down the drain. Dispose of contents and container in accordance with all local, regional, national and international regulations. For responsible disposal of paint and packaging visit paintback.com.au
SAFETY DATA SHEET	SDS available from the Taubmans Website taubmans.com.au/painters/all-weather

DISCLAIMER

*Taubmans All Weather® is guaranteed against blistering, flaking or peeling if applied on suitable and properly prepared surfaces according to printed directions. This guarantee applies to the owner of the house/property to which the paint has been applied and is available as long as the owner owns and lives in the house/property. The benefits provided under this guarantee are not transferable. Proof of purchase is required. This guarantee is given by PPG Industries Australia Pty Limited. This guarantee only applies to residential properties within Australia. This guarantee applies to defects in the manufacture or formulation of the paint and does not cover paint failure caused by factors beyond our control. If this guarantee is not met, we will replace the paint or refund your money. We are not liable for the cost of labour or any other direct or indirect loss or damage arising from a breach of this guarantee. Customers are responsible for all costs of claiming under this guarantee. To claim, customers must write to us or call our Customer Care number to request a claim form. The benefits provided by this guarantee are in addition to other rights and remedies under the law. If you are a consumer within the meaning of the Australian Consumer Law: Our goods come with guarantees that cannot be excluded under the Australian Consumer Law. You are entitled to a replacement or refund for a major failure and for compensation for any other reasonably foreseeable loss or damage. You are also entitled to have the goods repaired or replaced if the goods fail to be of acceptable quality and the failure does not amount to a major failure.

Colorbond® and ZINCALUME® are registered trade marks of BlueScope Steel Limited.

Any information provided by PPG Industries Australia Pty Limited and its related entities relating to PPG products or their use and application (for example, information contained in a PPG paint system, Specification, or Data Sheet) is accurate and reliable at the time of publication. However, such information is general in nature. You must ensure that the information is current and suitable for the specific conditions for your project. If you need technical information for your circumstances, you should contact Taubmans Customer Service. PPG Industries Australia Pty Limited and its related entities are not liable for any loss (including indirect, special or consequential loss, or loss of profits), expense, or damage suffered in connection with (a) such information, or (b) any information provided by a third party (including where that information is provided on a PPG website). Nothing in this disclaimer restricts, excludes or modifies or purports to restrict, exclude or modify any statutory rights under any applicable law including the Competition and Consumer Act 2010 (Cth) or the operation of any express guarantee.

CUSTOMER SERVICE/COMPANY CONTACT

Taubmans Customer Service: 131 686 Further information: taubmans.com.au